


RX-531

Rualaix®

STOP-OXID

Rust Converter



## USE

Any kind of rusted metal surfaces

Surfaces should be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

## FEATURES

- Brown colour liquid
- Transforms rust and turns it into a black film
- Synthetic enamel can be applied over the converted rust with no risk of altering its adhesion.
- Its texture provides a homogeneous extension
- Not re-paintable on water-based finishes.
- Storage: 12 months year inside its original container and kept free from humidity.

## HOW TO USE

- Agitate before use.
- Apply with a brush, airless or roller.
- Remove any paint, excess rust and dirt from the surface.
- Clean using water and let dry.
- Apply the product.
- After 12 hours apply a coat of dissolvent enamel or mortar

## IDEAL FOR

- Transforming rust
- Treating rust on iron or steel elements

## INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY i1, HIGH PERFORMANCE ONE COMPONENT COATINGS WATER-BASED

LIMIT: 140G/L COV (2007); 140g/l COV(2010)  
This product contains 11,49 g/l COV max.



4l Pallet de 24 boxes  
of 4 x 4 l.

Pallet de 48 boxes  
of 9 x 750 ml.



**PREPARATION**  
Ready to use



**PERFORMANCE**  
15 - 30 m<sup>2</sup>



**FIRE CLASSIFICATION**  
D - s2 - d0 - Combustible



**TOOL CLEANING**  
Use water only



2.5 - 3.5



**VISCOSITY**  
400 - 600



**TIME FOR RE-PAINTING**  
12 Hr. (max. recommended 24 hrs)



**DENSITY**  
1.06 ± 0.07 g/ml